



# JOHNSEN'S OIL CHARGE FOR RETROFIT 12 OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 09/11/2015

Version: 1.1

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : JOHNSEN'S OIL CHARGE FOR RETROFIT 12 OZ.  
Product code : 6535

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Oil Charge

#### 1.3. Details of the supplier of the safety data sheet

Technical Chemical Company  
P.O. BOX 139  
Cleburne, Texas 76033  
T 817-645-6088

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Liquefied gas H280  
Repr. 1B H360

Full text of H-phrases: see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) : Danger  
Hazard statements (GHS-US) : H280 - Contains gas under pressure; may explode if heated  
H360 - May damage fertility or the unborn child  
Precautionary statements (GHS-US) : P201 - Obtain special instructions  
P202 - Do not handle until all safety precautions have been read and understood  
P280 - Wear protective gloves, protective clothing, eye protection, face protection  
P308+P313 - If exposed or concerned: Get medical advice/attention  
P405 - Store locked up  
P410+P403 - Protect from sunlight. Store in a well-ventilated place  
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.  
P251 - Pressurized container: Do not pierce or burn, even after use  
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

#### 2.3. Other hazards

Other hazards not contributing to the classification : Contains gas under pressure; may explode if heated. May Cause frostbite in contact with skin. May Cause frostbite in contact with skin. (Liquid form can be ejected if the aerosol can is not held upright during use.) Warning. Intentional misuse and inhalation abuse may cause cardiac or central nervous systems effects. Warning. None under normal conditions.

#### 2.4. Unknown acute toxicity (GHS US)

No data available

### SECTION 3: Composition/Information on ingredients

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
Ester	(CAS No) Proprietary	50 - 70	Not classified
1,1,1,2-Tetrafluoroethane	(CAS No) 811-97-2	30 - 50	Liquefied gas, H280
Proprietary Inhibitor Package	(CAS No) Proprietary	5 - 10	Not classified

# JOHNSEN'S OIL CHARGE FOR RETROFIT 12 OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS-US classification
Benzyl Butyl Phthalate	(CAS No) 85-68-7	1 - 5	Repr. 1B, H360 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

The exact percentage is a trade secret.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention.
- First-aid measures after inhalation : Allow victim to breathe fresh air. Allow the victim to rest.
- First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
- First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : May damage fertility or the unborn child.
- Symptoms/injuries after inhalation : Coughing. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause irritation or asthma-like symptoms. May cause respiratory irritation. Slight irritation.
- Symptoms/injuries after skin contact : Blisters. Causes skin irritation. May cause slight irritation . May cause moderate irritation. Red skin.
- Symptoms/injuries after eye contact : May cause slight eye irritation . May cause slight irritation.
- Symptoms/injuries after ingestion : May be harmful if swallowed and enters airways. May be fatal if swallowed and enters airways.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

No additional information available

#### 5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.
- Other information : NFPA Aerosol Level 1.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources.

##### 6.1.1. For non-emergency personnel

- Protective equipment : Gloves. Safety glasses.
- Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

- For containment : Dam up the liquid spill. Contain released substance, pump into suitable containers. Plug the leak, cut off the supply.
- Methods for cleaning up : Store away from other materials.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

# JOHNSEN'S OIL CHARGE FOR RETROFIT 12 OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed	: Pressurized container: Do not pierce or burn, even after use.
Precautions for safe handling	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not handle until all safety precautions have been read and understood. Obtain special instructions.
Hygiene measures	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product. Wash affected areas thoroughly after handling. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Proper grounding procedures to avoid static electricity should be followed. Comply with applicable regulations.
Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use.
Incompatible products	: Strong bases. Strong acids.
Incompatible materials	: Sources of ignition. Direct sunlight.
Storage area	: Store in a well-ventilated place.

#### 7.3. Specific end use(s)

Follow Label Directions.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### 8.2. Exposure controls

Appropriate engineering controls	: Local exhaust ventilation, vent hoods . Ensure good ventilation of the work station.
Personal protective equipment	: Gloves. Safety glasses. Avoid all unnecessary exposure.



Materials for protective clothing	: GIVE EXCELLENT RESISTANCE:
Hand protection	: Wear protective gloves.
Eye protection	: Chemical goggles or safety glasses.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: Wear appropriate mask.
Consumer exposure controls	: Avoid contact during pregnancy/while nursing.
Other information	: Do not eat, drink or smoke during use.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Liquid.
Color	: Red.
Odor	: Characteristic. Petroleum-like odour.
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 245 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 0.95

# JOHNSEN'S OIL CHARGE FOR RETROFIT 12 OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Solubility	: Insoluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: 0 - 0 cSt
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

### 9.2. Other information

VOC content	: 0 %
Gas group	: Liquefied gas

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Not established.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

1,1,1,2-Tetrafluoroethane (811-97-2)	
LC50 inhalation rat (mg/l)	> 2000 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	> 359300 ppm/4h (Rat; Literature study)

Benzyl Butyl Phthalate (85-68-7)	
LD50 oral rat	2330 mg/kg (Rat)
LD50 dermal rat	6700 mg/kg (Rat)
LD50 dermal rabbit	> 10000 mg/kg (Rabbit)
LC50 inhalation rat (mg/l)	> 6.7 mg/l/4h (Rat)

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Benzyl Butyl Phthalate (85-68-7)	
IARC group	3

Reproductive toxicity	: May damage fertility or the unborn child.
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: Coughing. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause irritation or asthma-like symptoms. May cause respiratory irritation. Slight irritation.
Symptoms/injuries after skin contact	: Blisters. Causes skin irritation. May cause slight irritation . May cause moderate irritation. Red skin.

# JOHNSEN'S OIL CHARGE FOR RETROFIT 12 OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/injuries after eye contact : May cause slight eye irritation . May cause slight irritation.  
Symptoms/injuries after ingestion : May be harmful if swallowed and enters airways. May be fatal if swallowed and enters airways.

### SECTION 12: Ecological information

#### 12.1. Toxicity

<b>1,1,1,2-Tetrafluoroethane (811-97-2)</b>	
LC50 fish 1	450 mg/l (LC50; 96 h)
EC50 Daphnia 1	980 mg/l (EC50; 48 h)
<b>Benzyl Butyl Phthalate (85-68-7)</b>	
LC50 fish 2	0.82 mg/l (LC50; 96 h)
EC50 Daphnia 2	0.97 mg/l (EC50; 48 h)

#### 12.2. Persistence and degradability

<b>JOHNSEN'S OIL CHARGE FOR RETROFIT 12 OZ.</b>	
Persistence and degradability	Not established.
<b>1,1,1,2-Tetrafluoroethane (811-97-2)</b>	
Persistence and degradability	Not readily biodegradable in water.
<b>Ester (Proprietary)</b>	
Persistence and degradability	Not established.
<b>Proprietary Inhibitor Package (Proprietary)</b>	
Persistence and degradability	Not established.
<b>Benzyl Butyl Phthalate (85-68-7)</b>	
Persistence and degradability	Readily biodegradable in water. Forming sediments in water. Biodegradability in soil: no data available. Adsorbs into the soil.

#### 12.3. Bioaccumulative potential

<b>JOHNSEN'S OIL CHARGE FOR RETROFIT 12 OZ.</b>	
Bioaccumulative potential	Not established.
<b>1,1,1,2-Tetrafluoroethane (811-97-2)</b>	
BCF other aquatic organisms 1	5 - 58 (BCF)
Log Pow	1.06 (OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
<b>Ester (Proprietary)</b>	
Bioaccumulative potential	Not established.
<b>Proprietary Inhibitor Package (Proprietary)</b>	
Bioaccumulative potential	Not established.
<b>Benzyl Butyl Phthalate (85-68-7)</b>	
BCF fish 1	188 (BCF; 408 h)
BCF fish 2	663 (BCF; 504 h)
BCF other aquatic organisms 1	26 - 270 (BCF)
Log Pow	3.57 - 5.8
Bioaccumulative potential	Not established.

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

Other information : Avoid release to the environment.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

Ecology - waste materials : Avoid release to the environment.

# JOHNSEN'S OIL CHARGE FOR RETROFIT 12 OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground):	UN1078, Refrigerant gases, n.o.s., 2.2, Limited Quantity
ICAO/IATA (air):	UN1078, Refrigerant gases, n.o.s., 2.2, Limited Quantity
IMO/IMDG (water):	UN1078, Refrigerant gases, n.o.s. (1,1,1,2-Tetrafluoroethane), 2.2
Special Provisions:	T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the applicable liquefied compressed gases are authorized to be transported in portable tanks in accordance with the requirements of 173.313 of this subchapter.

#### 14.2. UN proper shipping name

Proper Shipping Name (DOT)	: Refrigerant gases, n.o.s.
Transport hazard class(es) (DOT)	: 2.2 - Class 2.2 - Non-flammable compressed gas 49 CFR 173.115
Hazard labels (DOT)	: 2.2 - Non-flammable gas



DOT Symbols	: G - Identifies PSN requiring a technical name
DOT Special Provisions (49 CFR 172.102)	: T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the applicable liquefied compressed gases are authorized to be transported in portable tanks in accordance with the requirements of 173.313 of this subchapter.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 304
DOT Packaging Bulk (49 CFR 173.xxx)	: 314;315

#### 14.3. Additional information

Other information	: No supplementary information available.
-------------------	---

#### Overland transport

No additional information available

#### Transport by sea

DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
-----------------------------	---

#### Air transport

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

JOHNSEN'S OIL CHARGE FOR RETROFIT 12 OZ.	
SARA Section 311/312 Hazard Classes	Sudden release of pressure hazard Delayed (chronic) health hazard Immediate (acute) health hazard
1,1,1,2-Tetrafluoroethane (811-97-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
SARA Section 311/312 Hazard Classes	Sudden release of pressure hazard Immediate (acute) health hazard

#### 15.2. International regulations

##### CANADA

JOHNSEN'S OIL CHARGE FOR RETROFIT 12 OZ.	
WHMIS Classification	Class A - Compressed Gas
1,1,1,2-Tetrafluoroethane (811-97-2)	
WHMIS Classification	Class A - Compressed Gas

#### EU-Regulations

No additional information available

# JOHNSEN'S OIL CHARGE FOR RETROFIT 12 OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Repr.Cat.2; R61

Repr.Cat.3; R62

Full text of R-phrases: see section 16

### 15.2.2. National regulations

No additional information available

### 15.3. US State regulations

JOHNSEN'S OIL CHARGE FOR RETROFIT 12 OZ.	
U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No

1,1,1,2-Tetrafluoroethane (811-97-2)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

Ester (Proprietary)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

Proprietary Inhibitor Package (Proprietary)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

Benzyl Butyl Phthalate (85-68-7)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

## SECTION 16: Other information

Other information : None.

Full text of H-phrases:


Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Liquefied gas	Gases under pressure Liquefied gas
Repr. 1B	Reproductive toxicity Category 1B
H280	Contains gas under pressure; may explode if heated
H360	May damage fertility or the unborn child
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

NFPA health hazard

: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard

: 0 - Materials that will not burn.



# JOHNSEN'S OIL CHARGE FOR RETROFIT 12 OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

NFPA reactivity : 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently.

### HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 0 Minimal Hazard

Physical : 1 Slight Hazard

Personal Protection : B

SDS US (GHS HazCom 2012) - TCC

*The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product*

*Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.*